

## Accessory products - Valve Application Chart

## Europe - Edition 1

	Part number	Content  10 straight nickel plated valve L. 40mm	replacement for Alcoa Wheels P/N's beginning with:				
I m	GAX40MS00N		8105	8115	8125	8185	8355
L Hex 14	GAX54MSooN	10 straight nickel plated valve L. 54mm	7734	7834	8185	8825	
Hex 14	GAX6oMSooN	10 straight nickel plated valve L.60mm	8825	8925			
1	GAX8 <sub>3</sub> MSooN	10 straight nickel plated valve L.83mm (WorkHorse® Wheels)	886570	886580	896570	896580	
1	GAX70MS07N2	10 nickel plated valve with 7° angle	8745	8865	8965		
1 / / / / / / / / / / / / / / / / / / /	GAX70MS27N	10 nickel plated valve with 27° angle	8745	8845	8855	8945	8955
40,5	GAX70MS45N	10 nickel plated valve with 45° angle	6634	8835	8935		
Hex 14	GAX70MS60N	10 nickel plated valve with 60° angle	6632	8735	8835	8935	

	Part number	Content	replacement for Alcoa Wheels P/N's beginning with:
1.70 or 150 mm	GAX85	10 nickel plated valve extension L.20mm	
	GAX09150	10 x 150 mm POM plastic valve extension	
	GAX09070	10 x 70 mm POM plastic valve extension	



Recommended installation torque: between 12 and 15 Nm  $\,$ 

For more information we refer to our Alcoa Wheels Service Manual http://www.arconic.com/alcoawheels/europe/pdf/en/Alcoa\_Wheel\_Service\_manual\_English.pdf

## **Arconic Wheel and Transportation Products**

Tel. +32 11 458 478 E-mail: info.wheels@arconic.com www.alcoawheelseurope.com www.alcoafleet.eu

